

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/045955 A1

(51) International Patent Classification⁷: **H01M 2/16**,
2/18, 10/28

(21) International Application Number:
PCT/IB2003/005023

(22) International Filing Date:
5 November 2003 (05.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): **HIBAR
SYSTEMS LTD.** [CA/CA]; 35 Pollard Street, Richmond
Hill, Ontario L4B 1A8 (CA).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **SLIVAR, Djuro**
[CA/CA]; 165 Reiber Court, Waterloo, Ontario N2N 6N2
(CA).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,

CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SEPARATOR FOR CYLINDRICAL CELLS

(57) Abstract: Separator for cylindrical cell of the outwardly guided type, wherein a sheet material is wound around a mandrel, and starting from the winding step till the insertion of the separator into the cell, an outward support is used that renders the binding of the neighboring turns of the separator winding unnecessary, and the separator sheet has an extended lower portion, wherein the extension is at least equal to the radius of the separator cylinder, and this extended portion is wetted with distilled or de-ionized water and wetted until the material softens and the winding and the mandrel are rotated and the bottom part is folded back and heat fused to close the separator cylinder.



WO 2005/045955 A1